

Adhesives and Sealants

Polyken 44 Premium Spray Adhesive



Rubber-Based Aerosol Spray Adhesive
Spray Pattern: Lace
 Low-VOC formulation. Fast skin, fast grab. Low soak-in. Good UV, moisture, and oxidation resistance.

Uses: Temporary and permanent bonding. Bonds foils and metals to fibrous and paper insulation, fabrics, leather, rubber, and wood to various other substrates. Prime surfaces for flashing tape or pipe wrap installation.

Color: Water White
% Solids: 28%
VOC Content: <55%
Maximum Operating Temperature: 180° F

Polyken 1027 Brush-on Primer



Butyl-Based Brush-On Primer
 Non-toxic, Non-polluting. Easy to apply. Dries to a uniform, slightly tacky surface.

Uses: Prime surfaces for flashing tape installation particularly for OSB, brick, gypsum board, or concrete. Also recommended to prime pipe surfaces prior to tape wrapping in corrosion protection applications.

Color: Black
% Solids: 30%
Solvent: V M and P Naptha
VOC Content: 4.9 lb/gallon
Maximum Operating Temperature: 185° F
Standard Sizes: 1 Qt or 1 Gal Pail

Film Tapes

Berry Plastics 555 FlexFix™ UL181B-FX



Backing: Printed OPP Film
Adhesive: Acrylic
 Excellent tensile and shear properties. High adhesion. Resists lifting and flagging. Mold resistant. **Low VOC.**

Uses: Seals Class 1 Flexible Duct and connectors. Adheres well to foam pipe and bubblewrap insulation materials. **UL181B-FX Listed.**

Thickness: 3.1 mils (78.74 mic)
Adhesion to Steel: 45 oz/in (4.93 N/cm)
Tensile: 34 lb/in (59.64 N/cm)
Operating Temperature: 10° - 210° F
Colors: Black, Metallic
Standard Sizes: 48mm x 110M, 3in x 110M

Berry Plastics 444 Line Set Tape



Backing: OPP Film
Adhesive: Acrylic
 UV Resistant. Excellent tensile and shear properties. High Adhesion. Resists lifting and flagging. Mold resistant. Available printed or unprinted. **Low VOC.**

Uses: Designed specifically for wrapping and protecting outdoor line sets for heating, ventilation, and cooling systems.

Thickness: 3.0 mils (76.2 mic)
Adhesion to Steel: 45 oz/in (4.92 N/cm)
Tensile: 32 lb/in (56.04 N/cm)
Operating Temperature: 10° - 210° F
Colors: Black (Printed or Unprinted)
Standard Sizes: 48mm x 55M