

# B-Vent Systems

B-Vent systems use room air to support combustion and exhaust their flue products to the outdoors via a single pipe. B-Vent heaters can mount anywhere you have access to an existing flue or where you can install a vent run through the roof. The ability to attach to an existing flue makes a B-Vent system

an excellent replacement for an inefficient oil or wood stove. Though less efficient than other technologies – because they draw the already-heated room air to support combustion – B-Vent systems may be installed as the primary heating system.

## Conventional Vent Counterflow Wall Furnaces

Counterflow wall furnaces circulate warmth at floor level to provide comfort at a fraction of the cost of electric heat. The front panels remove easily for

cleaning and servicing. Choose standing pilot or electronic ignition. Optional side and rear registers help disperse heat to other areas. Requires electricity.

Natural Part #	LP Part #	Model Number	Input Btu	Temperature Control	Ignition System	Approx. Ship Wt.
<b>0239965</b>	<b>0239966</b>	FAW-40-SPP	40,000	Wall Thermostat, 24V	Standing Pilot/Piezo	110 lb.
		FAW-40-IP	40,000	Wall Thermostat, 24V	Intermittent Pilot/Electronic	110 lb.
<b>0239927</b>	<b>0239928</b>	FAW-55-SPP	55,000	Wall Thermostat, 24V	Standing Pilot/Piezo	135 lb.
<b>0239929</b>	<b>0239930</b>	FAW-55-IP	55,000	Wall Thermostat, 24V	Intermittent Pilot/Electronic	135 lb.

### Accessories

Part #	Accessory Number	Description	Approx. Ship Wt.
	SOR-1	Side Outlet Register	2 lb.
	SOK-1	10" Side Outlet Kit	7 lb.
	ROK-1	10" Rear Outlet Kit	9 lb.
<b>0239932</b>	FVE-24	Vent Enclosure, 24 inch for FAW-40	7 lb.
<b>0239933</b>	FVE-34	Vent Enclosure, 34 inch for FAW-40	10 lb.
<b>0239934</b>	FVE-46	Vent Enclosure, 46 inch for FAW-40	14 lb.
	DV-651	Vent Enclosure, 14 inch for FAW-55	6 lb.
	DV-665	Vent Enclosure, 24 inch for FAW-55	9 lb.
	DV-666	Vent Enclosure, 36 inch for FAW-55	14 lb.
<b>0239935</b>	DV-648	Oval-To-Round Flue Adapter Kit	2 lb.
<b>0239942</b>	TRW	Wireless Remote Wall Thermostat	2 lb.



## B-Vent Gravity Wall Furnaces

Our economical Gravity Vented Furnaces utilize state-of-the-art technology for the highest fuel efficiency. This furnace

recesses into a wall or surface mounts with the optional kit. Heat two adjoining rooms with the GWT-50

Natural Part #	LP Part #	Model Number	Input Btu	Temperature Control	Ignition System	Approx. Ship Wt.
		GWT-25	25,000	Millivolt (T-Stat not Included)	Standing Pilot	75 lb.
<b>0239964</b>	<b>0239936</b>	GWT-35	35,000	Millivolt (T-Stat not Included)	Standing Pilot	81 lb.
<b>0239967</b>	<b>0240040</b>	GWT-50*	50,000	Millivolt (T-Stat not Included)	Standing Pilot	131 lb.
	<b>0239937</b>	Conversion Kit for GWT-50				

\*Dual wall (heats 2 rooms)

### Accessories

Part #	Accessory Number	Description	Approx. Ship Wt.
	GWRB-T	Remote Bulb Thermostat, Millivolt, Fits GWT-25, GWT-35 and GWT-50	1 lb.
<b>0239948</b>	GWTB-2*	Automatic Blower, Fits GWT-25, GWT-35 and GWT-50	8 lb.
	GWTH-25/35	Header (included with furnace), Fits GWT-25 and GWT-35	2 lb.
	GWTH-50	Header (incldued with furnace), Fits GWT-50	4 lb.
	GWTR-1	Rear Register Kit, Fits GWT-25 and GWT-35	5 lb.
<b>0239955</b>	GWTW-2	Out-of-Wall Installation Kit, Fits GWT-25 and GWT-35	23 lb.
<b>0239958</b>	TMV	Wall Thermostat, Millivolt - Reed Switch	2 lb.
<b>0239942</b>	TRW	Wireless Remote Wall Thermostat	2 lb.

\*GWT-50 model may use two blowers

