## **Mini-Brake**° Compact & Portable

Make big or small fabrications on the job with this lightweight and portable tool! The versatile Mini Brake produces bends up to 135 degrees in sheet metals, including aluminum, copper and 22-gauge galvanized steel. The brake's compact size can accommodate sheet metal stock up to 4-feet wide, in any length, because there is no fixed throat depth to contend with.

Use the Mini Brake anywhere on the job site, even on a truck tailgate, for a variety of fabricating tasks from large HVAC transitions to narrow roof flashing to structures as small as a 4-inch square. Strengthening ribs on the brake's anvil and apron assure consistent bends. A safety conscious, cam-over style clamping mechanism, similar to much larger shop-floor brakes, keeps the anvil secure in any position. Optional legs are available separately.



Compact size makes the Mini Brake suitable for use virtually anywhere on the job site. Extra wide feet offer stability even when operating on a truck tailgate.





A 5/16 in. (7.9 mm) plate steel apron & adjustable strengthening ribs on anvil assure uniform bends across width of material.



Accommodates sheet metal up to 48 in. (1.2 m) wide in any length. There is no fixed throat depth to contend with.



Versatile bending range accommodates compact fabrications as small as a 4-in. (101.6 mm) square.



The Mini Brake also bends metal roofing components and roof flashing including copper and aluminum.



Dual-direction, cam-over style clamps keep anvil secure in any position. This safety conscious feature prevents anvil from free falling or creating a pinching hazard.

Catalog Number	Description	Minimum Hem Bending Depth in. (mm)	Width. ft. (M)	Net Wt. Ibs. (kg)	
MB48A	Mini-Brake	1/2 (12.7)	4 (1.22)	72 (32.66)	
MBL	Leg Kit	_	_	18 (8.17)	
CAPACITIES	Material	Stainless Steel 24 Gauge	Galvanized Steel 22 Gauge		Mild Steel 22 Gauge
MB48A	inches (mm)	0.024 (0.61)	0.034 (0.86)		0.030 (0.76)