

Z-FLEX® Features and Benefits

Z-Flex® Triple-Lock™ - Manufactured from 316TI, titanium stabilized, nickel, chromium, molybdenum stainless steel. Excellent resistance to the corrosive effects of flue gases. Suitable for extended periods at elevated temperatures without compromising corrosion resistance. A superior 29-4C grade stainless steel option is also available for conditions requiring greater resistance to acidic attack.

Construction - Triple-Lock™ Joint System; acknowledged to be the best available for strength and longevity. Stainless steel strip is spirally wound and mechanically joined together forming an air tight and leakproof **Triple-Lock™** seam. The corrugated outer wall provides crush protection during installation. The thin walled corrugated construction conducts heat quickly, aiding draft and discouraging the buildup of soot and other potentially corrosive residue.

Dimensions - Available in a range of sizes suiting all applications, from 2" to 24" diameter. Supplied in standard lengths up to 50 ft.

Smoothcore Construction - Twin Strip (2 ply) construction. The corrugated outer wall provides crush resistance during installation. The inner wall is smooth, permitting the smooth flow of flue gasses and impeding the build up of soot and other potentially corrosive residue. The inner and outer walls are joined by a **Triple-Lock™ Joint System**; acknowledged to be the best available for strength and longevity.

Approval - Z-Flex® Triple-Lock™ Chimney Liner Systems are listed and labelled by Underwriters Laboratories to UL1777 and ULC S635, Chimney Lining Systems for existing Masonry and Factory Built Chimneys.

Warranty - Lifetime Limited Warranty.



- Patented Triple-Lock™ design for strength
- Right sized packaging to lower shipping costs
- Best available materials/alloys
- 40+ years of manufacturing experience
- "Immediate" availability (24-72 hour lead time)
- Listed by Underwriters Laboratories

Z-FLEX® Chimney Liner Systems

Z-FLEX® Stainless Steel Chimney Kits Everything you need to get the job done right

Triple-Lock® Stainless Steel ALL FUEL APPLICATIONS

- **Z-FLEX®** Stainless Steel Chimney Liner Kits come complete with everything you need to quickly and easily install a professional venting system.
- **Patented Airtight Triple-Lock™ Construction**
Ideal for use with gas, oil, pellets and wood. (For use with coal, see warranty). The patented Triple-Lock™ construction is tested and listed by U.L. Triple-Lock™ is accepted by industry as the strongest joint system available.
- Manufactured from special high temperature and acid 316Ti resistant stainless.
- **Z-FLEX®**'s specially designed corrugations provide excellent flexibility while maintaining superior crush strength. The result is a clearly superior product offering incredible longevity.



Oil & Gas Kit Includes:

Stainless Steel
Liner
Chimney Flashing
Rain Cap
Mortar Collar
Part No.: 2OILKTX
Dia.: ____ | Lgth.: ____
Dia.: 3"-24" | Lengths: 50'



All Fuel Kit Includes:

Stainless Steel
Liner
Chimney Flashing
Rain Cap
Z-Lok Tee
Part No.: 2ZFLKIT
Dia.: ____ | Lgth.: ____
Dia.: 3"-24" | Lengths: 50'



Pellet Kit Includes:

Stainless Steel
Liner
Chimney Flashing
Rain Cap
Pellet Tee
Part No.: 2OILKTX
Dia.: ____ | Lgth.: ____
Dia.: 3"-24" | Lengths: 50'



All Fuel Insert Kit Includes:

Stainless Steel Liner
Chimney Flashing
Rain Cap
Insert Connector
Part No.: 2OILKTX_I
Dia.: ____ | Lgth.: ____
Dia.: 3"-24" | Lengths: 50'



Smoothcore Kit Includes

Smoothcore Stain-
less Steel Liner
Chimney Flashing
Rain Cap
Z-Lok Tee
Part No.: 2ZFSCKIT
Dia.: ____ | Lgth.: ____
Dia.: 3"-8" | Lengths: 50'



Universal All Fuel Insert Kit Includes:

Stainless Steel
Liner
Chimney Flashing
Rain Cap
Dripless Connector
Rigid Stacking Tee
Part No.: 2ZFLKTO
Dia.: ____ | Lgth.: ____
Dia.: 3"-24" | Lengths: 50'

